

QTY	SIZE	DESCRIPTION		
	9 IN		ABCX 531629	
	4 In.		ABCX 531629	
	10 in.		PLATE F	
	3 in	LD LMT		
	3 in	LT WT		
	1.5 in		SECURITY DEVISE ONLY (WITH 4.5" ARROW)	
	2.5in		SECURE BOTH HASPS	
			BEFOR MOVING CAR	
	3in		CLOSE AND LOCK	
			BOTH DOORS BEFORE	
			MOVING CAR	
	1.5in		STANDARD CAR SEAL ONLY (WITH 4.5" ARROW)	
	1.5in		OPENING	
			MAIN W 8-0 H 12-8	
			TOTAL W 16-0 H 12-8	
	2in		RELEASE ROD (WITH 4.5" ARROW)	
	2in		RETAINING VALVE (WITH 4.5" ARROW)	
	2in		2 INCH HF COMP SHOES	
	2in		LIFT AND	
			JACK HERE	(WITH 3.5" ARROW)
	3in		60 K	
	1.5in		UNLATCH	(with 4.5" arrow)
			TO CLOSE	
			DOOR	
	2in		DO NOT GROUND TO COUPLER	
			WHEN WELDING	
	2 in		EXH 17-0	(letters justified left)
			EXW 10-8	(numbers justified right)
			EW 9-7	16" max width
			IL 60-9	
			IW 9-6	
			IH 13-1	
			CU. FT. 7580	
	2in		EXH W 8-2	(letters justified left)
			EXW H 3-8	(numbers justified right)
			H 16-10	20" max width
			EMPTY C.G. 5-0	
			FLOOR H 3-8	
	1.5in		THIS CAR	(BLACK LETTERS WITH
			EXCESS HEIGHT	YELLOW BACKGROUND)
	1.5in			BLACK VINYL
	1.5in		DOOR LUBE	
			FCRH	