

**DECAL ORDER FORM**

Need	Qty	Size	Description
	2	9 In.	ABCX 531629
	2	4 In.	ABCX 531629
	2	10 In.	PLATE C
	2	3 In.	LD LMT LT WT
	2	3 In.	LB LB
	2	3 In.	KG KG
	2	3 In.	UTC
	2	1.5 In.	CAPY GAL US LITERS
	2	1.5 In.	LINE EXT HTRS
	2	1.5 In.	SPRG D-5 7 OUTER - 6 INNER
	2	1.5 In.	36 INCH WHLS
	4	1.5 In.	INCH HF COMP SHOES
	2	1.5 In.	BOT OPR VALVE
	2	1.5 In.	VALVE ATTACHED TO BOTTOM OUTLET
	2	1.5 In.	INLET (Vertical Cut)
	2	1.5 In.	OUTLET (Vertical Cut)
	2	1.5 In.	LEASED TO:
	2	4 In.	COMMODITY:
	2	1.5 In.	DOT 111A100W1
	2	2 In.	APPLIED BY
	2	1.5 In.	SPARK TESTED SHOP
	2	1.5 In.	CONVERTED ***
	2	1 In.	BUILT
	2	1.5 In.	MAX OPER HTR PSI EXT HTR PIPES NO INLET OR OUTLET PIPE CAPS REQ'D
	2	1 In.	PROTECT INTERIOR COATING WHEN ENTERING TANK WEAR CLEAN RUBBER OVERSHOES TOOLS MUST BE PROTECTED
	2	1 In.	CONSULT OWNER BEFORE REPAIRING OR CLEANING TANK BODY
	2	1 In.	CAUTION: DO NOT PUT STEAM OR BOILING WATER IN THIS TANK NOR REPAIR OR CLEAN WITHOUT CONSULTING OWNER
	2	1 In.	PAINTED SHOP SYSTEM
	2	1 In.	RULE 88.B.2 INSP. DATE BY (Due date no longer req'd)

	2	1	In.	A.E. SILL TESTE SHOP
	3	1	In.	GAUGE TABLE
	2	1	In.	BLT (Consolidation Block)
	1	1	In.	MANWAY STYLİ
	2	1.5	In.	LINING INSPECTED BY
	2	1.5	In.	REBUILT
	2	1	In.	SERVICE ABD EMERGENCY ABDW
	2	2	In.	GREEN SQUARES
	2	2	In.	WATER CAPY
	2	2	In.	LB KG
	2	1	In.	BRK PIPE LNTH
	2	1	In.	EXCESS FLOW VALVE 15,000 LBS/HR MINIMUM SHIPPING PRESSURE 50 PSI
	1	1.5	In.	HANDLE MUST BE LOCKED AND CHAINED IN CLOSED POSITION BEFORE LOADING
	1	1.5	In.	HANDLE MUST BE CHAINED TO UNDERSIDE OF CAR TO KEEP VALVE OPEN DURING UNLOADING
	1	1.5	In.	THIS CAR EQUIPPED WITH MIDLAND VALVE CLOSED <-----> OPEN
	2	1.5	In.	90 TON
	2	18.75 x 41.6875		Qualifiction Block w/ data
	2	18.75 x 41.6875		Qualifiction Block w/o data
				STATION STENCIL
				QUALIFIED DATE
				QUALIFICATION DUE
				TANK QUALIFICATION
				THICKNESS TEST
				SERVICE EQUIPMENT
				PRD: VALVE 75 PSI
				LINING
				88.B.2 INSPECTION
				STUB SILL INSPECTION